

# MOBIHEL<sup>®</sup>

... for the cars we love

## 2K HS HARDENERS

Multipurpose acrylic hardeners designed for use as B components in HS VOC Clearcoats. Ensure a smooth surface, excellent in depth drying and help achieve high gloss levels



PACKING DATA

MOBIHEL 2K HS HARDENER 4100

Packing: 6 x 0.5 l  
4 x 2.5 l

Index: 41958381  
41958313



MOBIHEL 2K HS HARDENER 4300

Packing: 6 x 0.5 l  
4 x 2.5 l

Index: 47774901  
47774903



MOBIHEL 2K HS HARDENER 4350

Packing: 4 x 2.5 l

Index: 47843803

MOBIHEL 2K HS HARDENER 4500

Packing: 6 x 0.5 l  
4 x 2.5 l

Index: 47088821  
47088813



HYGIENE & PERSONAL PROTECTION



TECHNICAL CHARACTERISTICS

Colour: Colourless

Product type: Isocyanate

Density: 1,019 – 1,040 g/ml



2K materials react with humidity; take care that all containers and tools are absolutely dry. While coating, the interior relative humidity should not exceed 80%.


NOTE

Please make sure to follow the recommendations and mixing ratios as stated in the TDS of each A component.


DRYING




Drying time at:




MOBIHEL 2K HS HARDENER 4350



MOBIHEL 2K HS HARDENER 4300



MOBIHEL 2K HS HARDENER 4100



MOBIHEL 2K HS HARDENER 4500

**SHELF LIFE**



**Shelf life:**

2 years

**SAFETY ADVICE**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P273 - Avoid release to the environment. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

**ONLY FOR PROFESSIONAL USE**

Version: 3 -17