









Technical information (08/24)

MOBIHEL PASSIVATOR

- Provides better adhesion of coating (steel sheet metal, galvanized steel and aluminium)
- Excellent corrosion protection
- Easy to apply
- Water-based
- Colour: Brown orange
- VOC compliant

	FE	ZN	AL
SUBSTRATE PREPARATION	 P220 - P280	 MOBIHEL ANTISILICONE CLEANER	 MOBIHEL ANTISILICONE CLEANER
	 MOBIHEL ANTISILICONE CLEANER	 P220 - P280	 P220 - P280
		 MOBIHEL ANTISILICONE CLEANER	 MOBIHEL ANTISILICONE CLEANER
		MOBIHEL PASSIVATOR	MOBIHEL PASSIVATOR

NOTE:

MOBIHEL PASSIVATOR can be done by coating the substrate with a cloth soaked in the PASIVATOR or by applying the PASIVATOR with a spray gun. After passivating wait for 7 - 10 min. (not more than 15 min!) then apply the filler.

	Shelf life:	2 years
---	--------------------	---------

2004/42/II B(a) (200) 1

EU limit value VOC for this type of products (category II B (a)) in the form, which is ready for application is **200 g/l** VOC of this product, prepared for use is **1 g/l**.

FOR PROFESSIONAL USE ONLY – See Safety Data Sheet

The data may vary under various conditions.

Any part of this information may change at any time without notice.

The information was derived from years of experience in the collaboration of Development and Technical Services and is the property of HELIOS Refinish.

We guarantee that the quality of work carried out according to our instructions delivers results while we disclaim any liability if any other products were used or if other factors influenced the final appearance.

The latest version of TDS supersedes all previous versions. You can obtain the latest version from general distributor in your country.

The user of this product should use the product in accordance with the laws and regulations for safety at work and waste management.

Version: 2024-2 (01.08.2024)

