









Technical information (08/24)

## MOBIHEL ANTIGRAVEL

- One component coating based on modified rubbers
- For protection of sills and wheel arches against stone chipping
- Resistant to salt, humidity, oil and benzine
- Over-coating possible immediately after drying
- Colour: grey and black
- VOC compliant

<b>SUBSTRATE PREPARATION</b>	
	 MOBIHEL ANTISILICONE CLEANER

	<b>Shaking:</b>	40x
	<b>Application with spray gun:</b>	3- 4 bar 2 - 3 layers
	<b>Application temperature:</b>	min 15°C
	<b>Flash-off:</b>	5 - 10 min/20°C
	<b>Drying time at 20°C:</b> <b>Drying time at 60°C:</b>	60 - 90 min 30 min
	<b>Shelf life:</b>	2 years

2004/42/II B(e) (840) 400

EU limit value VOC for this type of products (category II B (e)) in the form, which is ready for application is **840 g/l** VOC of this product, prepared for use is **400 g/l**.

FOR PROFESSIONAL USE ONLY – See Safety Data Sheet

The data may vary under various conditions.

Any part of this information may change at any time without notice.

The information was derived from years of experience in the collaboration of Development and Technical Services and is the property of HELIOS Refinish.

We guarantee that the quality of work carried out according to our instructions delivers results while we disclaim any liability if any other products were used or if other factors influenced the final appearance.

The latest version of TDS supersedes all previous versions. You can obtain the latest version from general distributor in your country.

The user of this product should use the product in accordance with the laws and regulations for safety at work and waste management.

Version: 2024-2 (01.08.2024)

