





Technical information (09/25)

HELIOS REFINISH 2K ADDITIVE EXTRA SLOW

- It is used for an excellent application properties at very high outside temperatures. (from 30 - 40°C) for all GRAVIHEL 2K PUR Top coats Binders and MOBIHEL 2K acrylic enamel.

	Stir well:	5% of the amount of thinner prescribed for each individual product (all GRAVIHEL 2K PUR TOP COATS and MOBIHEL 2K akrilyc enamel) is replaced with HELIOS REFINISH 2K ADDITIVE EXTRA SLOW
	Shelf life:	4 years

FOR PROFESSIONAL USE ONLY – See Safety Data Sheet

Close the packaging of the Hardener immediately after use, because the product reacts with air humidity and may cause defects in the product.
The data may vary under various conditions.

Any part of this information may change at any time without notice.

The information was derived from years of experience in the collaboration of Development and Technical Services and is the property of HELIOS Refinish.

We guarantee that the quality of work carried out according to our instructions delivers results while we disclaim any liability if any other products were used or if other factors influenced the final appearance.

The latest version of TDS supersedes all previous versions. You can obtain the latest version from general distributor in your country.

The user of this product should use the product in accordance with the laws and regulations for safety at work and waste management.

Version: 2025-21 (02.09.2025)