Technical information (11/26)

HELIOS REFINISH ELASTIC ADDITIVE

- Used to increase the elasticity of the coating when painting plastic parts.
- 20- 30% to be added to a component A - 2K FILLERS or 2K CLEARCOATS

		2K FILLER or 2K CLEARCOAT
	**Mixing ratio:**	A hardener to be added in the prescribed ratio of the A component used. When using of HELIOS REFINISH 2K elastic additive VOC the drying time is slightly extended.
	**Shelf life:**	4 years

FOR PROFESSIONAL USE ONLY – See Safety Data Sheet

Close the packaging of the Hardener immediately after use, because the product reacts with air humidity and may cause defects in the product.
The data may vary under various conditions.
Any part of this information may change at any time without notice.
The information was derived from years of experience in the collaboration of Development and Technical Services and is the property of HELIOS Refinish.
We guarantee that the quality of work carried out according to our instructions delivers results while we disclaim any liability if any other products were used or if other factors influenced the final appearance.
The latest version of TDS supersedes all previous versions. You can obtain the latest version from general distributor in your country.
The user of this product should use the product in accordance with the laws and regulations for safety at work and waste management.

Version: 2026-21 (09.11.2026)

KANSAI HELIOS Slovenija d.o.o., Količevo 65, 1230 Domžale Slovenia
T: + 386 1 722 40 00, E: office@helios-refinish.com, www.helios-refinish.com

Member of KANSAI HELIOS